

General Data

Description Value

General Information

Product name: QF 50-14-MTSF-150_17.5HP With 3~
Price: Price on req.

Technical

Speed for pump data: 2900 1/min
Actual calculated flow:
Resulting head of the pump:
Head max.: 160.1 m
Stages: 14
Curve tolerance: ISO 9906.2012 3B
Pump type: QF 50
Valve: Pump with built-in non-return valve

Liquid

Pumped liquid: Water
Liquid temp. range: 20 °C
Density: 998.3 kg/m³

Materials

Pump: Stainless steel DIN W.-Nr. 1.4301 AISI 304
Impeller: Stainless steel DIN W.-Nr. 1.4301 AISI 304
Motor: CI FG-260

Installation



Max. ambiente temperature: 40 °C
Max. Operating Pressure : Maximum 0.67m (67 bar)
Pump outlet: Rp 3
Motor diameter: 150 mm

Electrical Data

Motor type: MTSF-150_17.5HP
No poles: 2
Rated Power: 13 kW
Frequency: 50 Hz
Rated Volt.: 380 V
Rated Current: 30.1 A
Power Factor: 0.84
Eff.: 80 %

Others

Net weight
Net Pump Weight: 33 kg



Name	mm
C	1614
B	779
A	2393
D	145
E*	143

E = Maximum diameter of pump inclusive of cable guard & motor

* Maximum diameter of pump with one motor cable

** Maximum diameter of pump with two motor cable

Customer

Supplier

Company name
Department
Issued by
Phone number
Fax no.
e-mail address

Dimension QF


Product No.: QF 50 SERIES

Inlet / outlet

Suction port	Discharge port
Rp 3	Rp 3
DN 65 PN 16/40	DN 65 PN 16/40

Dimensions mm

C	1614
B	779
A	2393
D	145
E*	143
E**	145



E* = Maximum diameter of pump
inclusive of cable guard & motor

E** = Maximum diameter of pump
with two motor cable