

VN/VL 9 - 50 HZ

TECHNICAL DATA

Electric pump model		Number of stages	MOTOR POWER		INPUT POWER	Capacitor		RATED CURRENT		
								Single-phase 220-240 V	Three-phase	
Single-phase	Three-phase		[kW]	[HP]	[kW]	μF	V		220-230 V	380-415 V
VN-VL 9/3	VN-VL 9/3T	3	1.1	1.5	1.44	30	450	6.9	4.5	2.6
VN-VL 9/4	VN-VL 9/4T	4	1.5	2	1.86	35	450	9.7	5.5	3.2
VN-VL 9/5	VN-VL 9/5T	5	2.2	3	2.3	45	450	10.5	8.7	5
VN-VL 9/6	VN-VL 9/6T	6	2.2	3	2.68	45	450	11.9	9.2	5.3
-	VN-VL 9/7T	7	3	4	3.16	-	-	-	10.2	5.9
-	VN-VL 9/8T	8	3	4	3.54	-	-	-	10.9	6.3
-	VN-VL 9/9T	9	3	4	3.91	-	-	-	11.8	6.8

DIMENSIONS AND WEIGHTS

Electric pump			Weight* [Kg]		Packaging		
1~	3~	Lt [mm]	1~	3~	L [mm]	B [mm]	H [mm]
VN 9/3	VN 9/3T	504	17.25	16	720	230	175
VN 9/4	VN 9/4T	584	20.25	18.25	720	230	175
VN 9/5	VN 9/5T	614	22.25	21	800	230	195
VN 9/6	VN 9/6T	644	23	21.5	800	230	195
-	VN 9/7T	674	-	24	800	230	195
-	VN 9/8T	704	-	24.75	800	230	195
-	VN 9/9T	734	-	25.5	800	230	195

* Electric pump weight without float switch

Electric pump			Weight [Kg]		Packaging		
1~	3~	Lt [mm]	1~	3~	L [mm]	B [mm]	H [mm]
VL 9/3	VL 9/3T	488	15.75	14.6	720	230	175
VL 9/4	VL 9/4T	568	18.75	16.75	720	230	175
VL 9/5	VL 9/5T	598	20.5	19.35	800	230	195
VL 9/6	VL 9/6T	628	21.25	20	800	230	195
-	VL 9/7T	658	-	21.85	800	230	195
-	VL 9/8T	688	-	22.5	800	230	195
-	VL 9/9T	718	-	23	800	230	195

DIMENSIONAL DRAWINGS

